

G-2500 Wedge Barrier



G-2500 Series

- ASTM F2656-20 M50 P1 Certified
- Electro-Mechanical (EM)
- 8'-0" to 14'-0" True Blocking Width
- Hot-Dip Galvanize or Color Coat to Specifications
- 24" (610mm) Depth
- Manual Operation without Tools

Features

- Bi-Directional Flashing Lights
- EFO Deploy to Secure Position ≤ 1.5 Second (EM)
- IP 68 Rated Submersible Motor
- Design Allows for Less Stress on Barrier Parts from Vehicle Traffic

Benefits

- Low Maintenance
- No Rebar Needed for Installation
- No Actuator, Springs, Pneumatics or Assists Required
- No Chains:
Allows the Barrier to be Installed on Sloped Areas



Additional Options

- Touchscreen Controls
- Basic Controls
- Wrong Way Vehicle Loop
- Suppression Vehicle Loop
- Over Speed Detection
- Heat Trace
- Sump Pump
- Installation Kit
- Battery Backup
- Remote EFO
- AC/Fan Unit

Patent Pending

G-2500 Wedge Barrier



HQ: 3200 East State Hwy 29
Burnet, TX 78611
Offices: Middle East



www.gibraltarp.com



info@gibraltarp.com
(800) 495-8957